





CATEGORY	DESCRIPTION	P/N #
CONNECTOR	D-SUB 9Pin Female, V/A, T/H	DB609F-21XX0-00XX

REV.	ECN NO	DESCRIPTION	REVISED	DATE
A01		New Release	Luguan	2009.11.06



SPECIFICATIONS

- CONTACT CURRENT RATING:3 Amperes.
- DIELECTRIC WITHSTANDING VOLTAGE:AC 1000/60sec.r.m.s.
- INSULATION RESISTANCE:5000 Medohms MIN.AT DC 500V.
- CONTACT RESISTANCE:25 Milliohms MAX.
- TEMPERATURE:-55°C TO +105°C.
- GROUNDING SCREW TORQUE:3Kg MIN.
- SOLDER HEAT RESISTANCE:WAVE SOLDERING 260° 10sec.
- TO CONFORM TO THE "SoNY" DIRECTIVE.
- GREEN PRODUCT IDENTIFICATION LABEL IN PACKING: **G.P. PASS**



Recommend PCB Layout  
(Jack Top View)  
Tolerance: ±0.05mm  
Recommend PCB Thickness: 1.6mm

e	Screw	2	Brass	Ni Plating	
d	Terminal	9	Brass, T=0.2mm	See Table 1	
c	Shell	1	SPCC, T=0.4mm	Ni Plating	
b	Rivet	2	Brass	Ni Plating	
a	Housing	1	PBT UL94V-0	Black	
NO.	PART NAME	Q'TY	MATERIAL	PLATING & COLOR	Remark

UNLESS OTHERWISE SPECIFIED TOLERANCES			SCALE:1/1	UNIT: mm	DWG.NO:
DECIMALS:	ANGLES:		SIZE: A3	PAGE:1 OF 1	REV:A01
X : ±0.5	X : ±2°		APPROVED BY	CHECKED BY	PREPARED BY
X.X : ±0.3	X.X : ±1°		WYX	PJ	Luguan
X.XX : ±0.2			<b>CUSTOMER COPY</b>		

Product Drawing  
ALEXTRONIC

W-061-736		
-----------	--	--