






CATEGORY	DESCRIPTION	P/N #
CONNECTOR	Modular Jack, 8P8C, Straddle DIP	MJ881R-11110-002C

REV.	ECN NO	DESCRIPTION	REVISED	DATE
A01		New Release	XSY	2009.07.15



SPECIFICATIONS:

1. RJ Electrical Characteristics
 - 1-1: Voltage: 150V AC RMS
 - 1-2: Current Rating: 1.5A
 - 1-3: Contact Resistance: 40mΩ MAX.
 - 1-4: Insulation Resistance: 500MΩ MIN.
 - 1-5: Dielectric Withstang Voltage :1000V AC
 - 1-6: Operature Temperature: -40°C~80°C



Recommend PCB Layout
(Jack Top View)
Tolerance: ±0.05mm

e	LED O2	1		Green
d	LED O1	1		Yellow
c	Shielding	1	Brass, T=0.2mm	Ni Plating
b	Terminal	8	Phosphor Bronze, T=0.3mm	Au/Tin Plating
a	Housing	1	LCP UL94V-0	Black
NO.	PART NAME	Q'TY	MATERIAL	PLATING & COLOR

UNLESS OTHERWISE SPECIFIED TOLERANCES		SCALE: 1/1 UNIT: mm		DWG. NO: WI-061-515	
DECIMALS:	ANGLES:	SIZE: A3	PAGE: 1 OF 1	REV: A01	
X : ±0.5	X : ±2°	APPROVED BY	WYX	CHECKED BY	PJ
X.X : ±0.3	X.X : ±1°				PREPARED BY XSY
X.XX : ±0.2		CUSTOMER COPY			

Product Drawing
ALEXTRONIC