







CATEGORY	DESCRIPTION	P/N #
CONNECTOR	RJ45 Over USB ,Right Angle, 4.65 SUS SHELL	MU461R-21240-0010

▲A0Z 原料號 2MU21R-02B53-010
變更號 MU461R-21240-0010

REV.	ECN NO.	DESCRIPTION	REVISED	DATE
A1		新訂圖面	XSJ	2008.07.23
A02	ECN090810010	修正圖面,變更料號	Luguan	2009.08.10



Recommend PCB Layout
(Jack Top View)
Tolerance: ±0.05mm
Recommend PCB Thickness: 1.6mm

- SPECIFICATIONS:
- 1.RJ ELECTRICAL CHARACTERISTICS
- 1-1:VOLTAGE:150V AC RMS
 - 1-2:CURRENT RATING:1.5A
 - 1-3:CONTACT RESISTANCE:30mΩ MAX.
 - 1-4:INSULATION RESISTANCE:500MΩ MIN.
 - 1-5:DIELECTRIC WITHSTANG VOLTAGE :1000V AC
 - 1-6:OPERATURE TEMPERATURE:-40°C~80°C
 - 1-7:DURABILITY:500 MATING CYCLES MIN.
- 2.USB ELECTRICAL CHARACTERISTICS
- 2-1:VOLTAGE:30V AC RMS
 - 2-2:CURRENT RATING:1.5A
 - 2-3:CONTACT RESISTANCE:30mΩMAX.
 - 2-4:DIELECTRIC WITHSTANG VOLTAGE:500V AC
 - 2-5:INSULATION RESISTANCE:1000MΩ MIN.
 - 2-6:OPERATURE TEMPERATURE:-55°C~85°C
 - 2-7:DURABILITY:1500 MATING CYCLES
 - 2-8:"▲" IS IMPORTANT DIMENSIONS

g	USB	1	2UB142-FB020-00	Terminal: Brass C2680, T=0.25mm, Plating: 平均1u" Housing: PBT4830 UL94V-0, Color: Black Shell: Brass C2680, T=0.3mm, Plating: Ni 50u" MIN.		
f	SHIELDING	1	1SH-MJ4500-20	SUS304 T=0.25mm		
e	LED	1	1TM-RJLED-02		Green	
d	LED	1	1TM-RJLED-01		Yellow	
c	RJ INSERT	1	1MO-MJ4501-DO	Terminal: Phosphor Bronze C5191, T=0.30mm, Plating: Gold Flash Housing: PBT4830 UL94V-0, Color: Black		
b	COVER	1	1HS-MU4500-00	PBT4830 UL94V-0	Black	
a	HOUSING	1	1HS-MU4065-00	PBT4830 UL94V-0	Black	
No.	PART NAME	Q'TY	PART NUMBER	MATERIAL	PLATING & COLOR	REMARK

Product Drawing			
ALEXTRONIC			
SCALE: 1/1	UNIT: mm	DWG. NO: WI-061-234	
SIZE: A3	PAGE: 1 OF 1	REV: A02	
APPROVED BY	CHECKED BY	PREPARED BY	
WYX	Pengjie	Luguan	
ENGINEERING COPY			

UNLESS OTHERWISE SPECIFIED TOLERANCES

DECIMALS: X :±0.3
X.X :±0.2
X.XX :±0.1
X.XXX :±0.05

ANGLES: X :±1°
X.X :±0.5°